



ROOF GOOP



Roof Goop is a high solids, elastomeric, trowel-grade sealant based on the latest 100% acrylic technology. It has excellent adhesion to various surfaces including asphalt roofing, metal, concrete, and wood.

Roof Goop is ideal for imbedding polyester mesh fabric to flashing around roof penetrations, skylights, and solar panel equipment. It's a one-step repair material for patching defective roof areas. It can be applied thick enough to encapsulate reinforcing fabric in two coats (applied in succession), allowing repair men / installers to complete the repair in a single trip.

Roof Goop comes in white and black, allowing it to dry quickly, with easy clean up using soap and water.

APPLICATION

All surfaces must be dry and free from dirt, dust, grease, oil, and other contaminants. Apply 2 heavy coats (60 to 80 wet mils), or more for proper repairs. When encapsulating polyester mesh fabric over a repair area, extend the Roof Goop a minimum of 2 to 3 inches beyond the fabric edge prior to imbedding. Where larger areas are to be reinforced, overlap the fabric 2 inches at edge for extra strength. Repairs can be top coated with other acrylic roof products and/or other colored roof coatings where necessary for aesthetics.



PRODUCT SPECS

- Elastomeric Hi-Build Mastic
- 100% Acrylic Resins
- Filler Using Ceramic Spheres
- One-Step Repair Material
- Easy Soap/Water Clean up
- Permanently Flexible
- Dries Quickly
- UV Stable

PRODUCT PROPERTIES

- **Solids by Volume:** 66% (ASTM D5201)
- **Tensile Strength:** 325 psi (ASTM D412)
- **Elongation:** 200% (ASTM D412)

LIMITATIONS

Do not apply if Roof Goop cannot cure prior to exposure to cold, rain, or heavy dew. Do not take internally. KEEP OUT OF REACH OF CHILDREN.



All Weather Surfaces
99-890 Iwaena St
Aiea, HI 96701

PH: 808-487-3043
FX: 808-486-1920
www.allweathersurfaces.com

